

Part number:  
**T910972**

**Copyright**

© 2011, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

February 21, 2011, 12:20 PM

**Corporate Headquarters**

FLIR Systems, Inc.  
27700 SW Parkway Ave.  
Wilsonville, OR 97070  
USA  
Telephone: +1-503-498-3547

**Website**

<http://www.flir.com>

**Customer support**

<http://support.flir.com>

**Legal disclaimer**

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply.

Information and equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited.



**General description**

Bluetooth Transmitter with METERLINK™  
Wirelessly transmits Voltage and Current readings to your FLIR high-definition infrared camera to incorporate meter readings with thermal images.  
For more info see [www.extech.com](http://www.extech.com)

METERLINK™ makes it easy for a thermographer to quickly take electrical readings using an Extech EX845 clamp meter and instantly record them right on an infrared image. METERLINK™ accelerates infrared inspections and diagnostics while adding value to your reports by increasing the amount of detail you provide.

**EX845 CAT IV Clamp Meter Features:**

- Patented built-in non-contact IR Thermometer design with laser pointer
- True RMS Current and Voltage measurements
- Peak hold captures inrush currents and Transients
- MultiMeter functions include AC/DC Voltage, Resistance, Capacitance, Frequency, Diode, and Continuity
- 1.7" (43mm) jaw opening for conductors up to 750MCM or two 500MCM
- 4000 count backlit display
- Features include Data Hold and Min/Max and Auto Power off
- Autoranging with manual range button
- Complete with CAT IV test leads, 9V battery, Type K probe (-22 to 572°F/-30 to 300°C), pouch case, and Professional Test Lead Set

**Professional Test Lead Features:**

- 8-Piece Professional Test Lead set
- Two 42" (1m) PVC lead extensions with shrouded banana plugs at both ends
- Two modular 4" (102mm) Heavy Duty test probe handles with 0.16" (4mm) banana plug tip
- Two standard size, alligator clips with insulated rubber boot
- Two extra large, double-insulated, alligator clips with sharp teeth for piercing insulated wire. Jaws open to 0.8" (20mm)

**Compatible with the following products**

- 40402-3001 FLIR P660 12°
- 40402-3002 FLIR P660 24°
- 40402-3003 FLIR P660 45°
- 40402-3101 FLIR P640 12°
- 40402-3102 FLIR P640 24°
- 40402-3103 FLIR P640 45°
- 40402-3202 FLIR P630 24°
- 40402-3302 FLIR P635 24°
- 40402-3402 FLIR P620 24°
- 40402-3403 FLIR P620 45°
- 40402-3801 FLIR B660 12°
- 40402-3802 FLIR B660 24°
- 40402-3803 FLIR B660 45°
- 40402-3902 FLIR B620 24°
- 40402-3903 FLIR B620 45°
- 40402-3501 FLIR SC660 12°
- 40402-3502 FLIR SC660 24°
- 40402-3503 FLIR SC660 45°
- 40402-3601 FLIR SC640 12°
- 40402-3602 FLIR SC640 24°
- 40402-3603 FLIR SC640 45°
- 40402-3702 FLIR SC620 24°
- 40402-3703 FLIR SC620 45°
- 55901-0102 FLIR T620 25° (incl. Wi-Fi)
- 55901-0103 FLIR T620 45° (incl. Wi-Fi)
- 55901-0402 FLIR T640 25° (incl. Wi-Fi)
- 55901-0403 FLIR T640 45° (incl. Wi-Fi)
- 45301-0202 FLIR T400 (30 Hz)



## EX845: Clamp meter + IR therm TRMS 1000A AC/DC

P/N: T910972

© 2011, FLIR Systems, Inc.  
All rights reserved worldwide.

### Compatible with the following products

- 45302-0201 FLIR T360 (30 Hz)
- 45305-0201 FLIR T300 (30 Hz)
- 45307-0202 FLIR T425 (30 Hz)
- 45601-0202 FLIR T425 (9 Hz)
- 45309-0201 FLIR T365 (30 Hz)
- 45602-0201 FLIR T365 (9 Hz)
- 45605-0201 FLIR T250 (9 Hz)
- 45606-0201 FLIR T200 (9 Hz)
- 45609-0201 FLIR T335 (9 Hz)
- 45605-0201-1 FLIR T250 (9 Hz) + EX845
- 45609-0201-1 FLIR T335 (9 Hz) + EX845
- 45309-0201-1 FLIR T365 (30 Hz) + EX845
- 45602-0201-1 FLIR T365 (9 Hz) + EX845
- 45307-0202-1 FLIR T425 (30 Hz) + EX845
- 45601-0202-1 FLIR T425 (9 Hz) + EX845
- 45311-0201 FLIR T335 (30 Hz)
- 45311-0201-1 FLIR T335 (30 Hz) + EX845
- 45303-0202 FLIR B400 (30 Hz)
- 45304-0201 FLIR B360 (30 Hz)
- 45306-0201 FLIR B300 (30 Hz)
- 45308-0202 FLIR B425 (30 Hz)
- 45603-0202 FLIR B425 (9 Hz)
- 45310-0201 FLIR B365 (30 Hz)
- 45604-0201 FLIR B365 (9 Hz)
- 45607-0201 FLIR B250 (9 Hz)
- 45608-0201 FLIR B200 (9 Hz)
- 45610-0201 FLIR B335 (9 Hz)
- 45607-0201-1 FLIR B250 (9 Hz) + MO297
- 45610-0201-1 FLIR B335 (9 Hz) + MO297
- 45604-0201-1 FLIR B365 (9 Hz) + MO297
- 45310-0201-1 FLIR B365 (30 Hz) + MO297
- 45603-0202-1 FLIR B425 (9 Hz) + MO297
- 45308-0202-1 FLIR B425 (30 Hz) + MO297
- 45312-0201 FLIR B335 (30 Hz)
- 45312-0201-1 FLIR B335 (30 Hz) + MO297
- 39903-1102 FLIR i60
- 39903-1102-1 FLIR i60 + EX845
- 39904-1202 FLIR b60
- 39904-1202-1 FLIR b60 + MO297
- 49001-0301 FLIR E40 (incl. Wi-Fi)
- 49001-0401 FLIR E50 (incl. Wi-Fi)
- 49001-0502 FLIR E60 (incl. Wi-Fi)
- 49001-0701 FLIR E40bx (incl. Wi-Fi)
- 49001-0801 FLIR E50bx (incl. Wi-Fi)
- 49001-0902 FLIR E60bx (incl. Wi-Fi)