


- Luminous Intensity Measurement: Include LED light and all visible light.


## Light Meter

TM-209

- Corrected LED day white light Spectrum



### DISPLAY

- 3 3/4 digits Backlit LCD with maximum reading 3999.
- Overload indication : "OL" .
- Low battery indication : "  " .

### FEATURES:

- According to JISC1609: 1993 and CNS 5119 general A class specifications.
- Spectral response close to CIE luminous spectral efficiency.
- Measuring intensities of illumination in unit of Lux or Foot-candle.
- Silicon photo diode and filter.
- Measuring light source include all visible light source.
- Cosine angular corrected.
- 99 records storage capacity.
- Luminous Intensity Measurement.
- Auto power off with disable function.
- Data hold.
- Max/Min/AVG hold.
- Reel time clock with calendar.
- Reel Zero function.
- Auto ranging.
- Many applications include: warehouses, factories, office buildings, restaurants, schools, library, hospitals, photographic, video, parking garages, museums, art galleries, stadiums, building security.

### Specifications

Light Source Selecting	Tungsten/Daylight, Fluorescent, 0~9 select rating
Measuring range	40,400,4,000,40,000,400,000Lux 40,400,4,000,40,000Foot-candel
Accuracy	3% ((Calibrated to standard incandescent lamp 2856°K◦ and corrected LED day while light spectrum)
	6% (other visible light source)
Meter size (LxWxH)	130*55*38mm
Sensor size (LxWxH)	80*55*25mm
Weight (including battery)	250g